

Z 10 (XL stands for XLong High Grade Heat Xchanger)
package included parts & accessories



Z10 spotlight pair
L. Flux: up to 1050lm each
Connection: Twin in series
Cable: \varnothing 6.5mm/80cm tinned copper



LPS 1212CCVRF DC/DC conv.
Voltage Input: 12-24VDC
Power: 80W max
Dimming: @ 433MHz 2xkey fobs



H05RN-F/IEC 60245-57/Rubber Cable
conductors: 4x1mm tinned copper
length: 2m



10094CB + 2 x Cable Glands
Connections: 8p
Insulation: Water resistant



Mounting Screws
Alloy: 8 x A4 - SS316
Long Shank Philips Hex Bit 90mm

Z 14, 15, 17 (XL stands for XLong High Grade Heat Xchanger)
package included parts & accessories



Z14, 15, 17 spotlight pair
L.Flux: up to 1440, 1440, 1800lm each
Connection: Twin in series
Cable: \varnothing 6.5mm/80cm tinned copper



LPS 1235CCVRF DC/DC conv.
Voltage Input: 12-24VDC
Power: 100W max
Dimming: @ 433MHz 2xkey fobs



H05RN-F/IEC 60245-57/Rubber Cable
conductors: 4x1mm tinned copper
length: 2m



10094CB + 2 x Cable Glands
Connections: 8p
Insulation: Water resistant



Mounting Screws
Alloy: 8 x A4 - SS316
Long Shank Philips Hex Bit 90mm

Z 19
package included parts & accessories



Z19 spotlight pair
Luminous Flux: 2000lm each
Connection: Twin in series
Cable: \varnothing 6.5mm/80cm tinned copper



LPS 1235CCVRF DC/DC conv.
Voltage Input: 12-24VDC
Power: 100W max
Dimming: @ 433MHz 2xkey fobs



H05RN-F/IEC 60245-57/Rubber Cable
conductors: 4x1mm tinned copper
length: 2m



10094CB + 2 x Cable Glands
Connections: 8p
Insulation: Water resistant



Mounting Screws
Alloy: 8 x A4 - SS316
Long Shank Philips Hex Bit 90mm

Z 24
package included parts & accessories



Z24 spotlight pair
Luminous Flux: up to 2400lm each
Connection: Twin in series
Cable: \varnothing 6.5mm/80cm tinned copper




LPS 1235CCVRF DC/DC conv.
Voltage Input: 12-24VDC
Power: 100W max
Dimming: @ 433MHz 2xkey fobs



1224VST
PWM 12-24VDC Regulator



H05RN-F/IEC 60245-57/Rubber Cable
conductors: 4x1mm tinned copper
length: 2m



10094CB + 2 x Cable Glands
Connections: 8p
Insulation: Water resistant



Mounting Screws
Alloy: 8 x A4 - SS316
Long Shank Philips Hex Bit 90mm

Z 4750 XLIR equipped with XL High Grade Heat Xchanger
package included parts & accessories



Z4750 XLIR spotlight pair / 12W each
Center wave length: 850nm
Connection: Twin in series
Cable: \varnothing 6.5mm/80cm tinned copper



LPS 1235CCV DC/DC conv.
Voltage Input: 12-24VDC
Power: 100W max
Dimming: N/A



H05RN-F/IEC 60245-57/Rubber Cable
conductors: 4x1mm tinned copper
length: 2m



10094CB + 2 x Cable Glands
Connections: 8p
Insulation: Water resistant



Mounting Screws
Alloy: 8 x A4 - SS316
Long Shank Philips Hex Bit 90mm

Z 45, 47, 55 all equipped with XL High Grade Heat Xchanger
package included parts & accessories



Z45, 47, 55 spotlight pair
L. Flux: 4300, 4900, 5500lm each
Connection: Twin in series
Cable: \varnothing 6.5mm/80cm tinned copper



a) 240MNW +320DRF DC/DC conv.
Voltage Input: 120-240VAC
Power: 240W max

OR



b) LPS-3048CCV+320DRF DC/DC conv.
Voltage Input: 12-24VDC
Power: 115W max w/dimming



H05RN-F/IEC 60245-57/Rubber Cable
conductors: 4x1mm tinned copper
length: 2x2m



10094CB + 2 x Cable Glands
Connections: 8p
Insulation: Water resistant



Mounting Screws
Alloy: 8 x A4 - SS316
Long Shank Philips Hex Bit 90mm